

FLP-1

"FLP" SERIES LOW PROFILE PLATFORMS



Low profile platforms, with 500 mm ramps, painted steel structure and chequered load surface. Ideal for weighing trolleys and pallet trucks thanks to the on/off ramps on both sides as well as the sideboards. The standard version is provided with approved load cells.

TECHNICAL FEATURES

- Fitted with 4 shear-beam 3500hm nickel-plated steel load cells, approved according to OIML R60 C3 standards (3000 divisions), IP67 protection degree. Chequered steel structure and load surface, oven-fire painted, RAL 5007 blue.
- Adjustable, anti-shock jointed feet and level.
- Power supply from 5 to 15 Vdc.
- Hermetic junction box, IP67 wiring with shielded 5m long cable for connection to the indicator.
- Fitted with sideboards and double on/off ramps.
- Upon request:
 - platform calibration service with weight indicator;
 - 3000e CE-M approval, to be combined always to the calibration service;
 - support column for indicator.

DETAIL 1



Installation example, with DFWL indicator and CSP38 column

VERSIONS

Available versions					
	l x w x h	N° celle	Max	d	M
Codice	(mm)	iv celle	(kg)	(g)	(g)*
FLPC-1	800x800x48	4x250kg	600	200	200
FLPA-1	1250x1000x48	4x2000kg	1500	500	500
FLPB-1	1250x1500x48	4x2000kg	2000	1000	1000

^(*) Divisions obtainable only with the relative options, in combination with Dini Argeo weight indicator.





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena • Italy Tel. +39.0536 843418

UAB REIMORA

MAINU 8 - 94101 - KLAIPEDA - LITHUANIA

Tel. +370 8 46 233806

info@reimora.lt

SALES AND TECHNICAL ASSISTANCE SERVICE